

Coudes

Coude 45 degrés

Resin Type: Derakane 411



#	DN (mm)	Pmax (bar)	Bend Angle (deg)	ID (mm)	OD (mm)	WT (mm)	RF	R (mm)	Article Number
1	25	16	45	25	33	4	2.0	50	EMS45-25-16/PE
2	40	16	45	40	50	5	2.0	80	EMS45-40-16/PE
3	50	16	45	50	60	5	2.0	100	EMS45-50-16/PE
4	65	16	45	65	77	6	2.0	130	EMS45-65-16/PE
5	80	16	45	80	92	6	2.0	160	EMS45-80-16/PE
6	100	16	45	100	112	6	2.0	150	EMS45-100-16/PE
7	125	16	45	125	139	7	1.5	190	EMS45-125-16/PE
8	150	16	45	150	166	8	1.5	225	EMS45-150-16/PE
9	200	10	45	200	216	8	1.5	300	EMS45-200-10/PE
10	200	16	45	200	222	11	1.5	300	EMS45-200-16/PE
11	250	10	45	250	266	8	1.5	375	EMS45-250-10/PE
12	250	16	45	250	274	12	1.5	375	EMS45-250-16/PE
13	300	10	45	300	318	9	1.5	450	EMS45-300-10/PE
14	300	16	45	300	326	13	1.5	450	EMS45-300-16/PE

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.