

# Rotec Blind Flenzen

Hars Derakane 470

Drilling Standard: JIS B2220 30K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	150	25	325	275	12	27	35	BFC-150-25/30K
2	150	32	325	275	12	27	40	BFC-150-32/30K
3	200	25	380	320	12	27	44	BFC-200-25/30K
4	200	32	380	320	12	27	48	BFC-200-32/30K
5	250	25	450	390	12	33	52	BFC-250-25/30K
6	250	32	450	390	12	33	60	BFC-250-32/30K
7	300	25	540	450	16	33	60	BFC-300-25/30K
8	300	32	540	450	16	33	68	BFC-300-32/30K
9	350	25	585	495	16	33	68	BFC-350-25/30K
10	350	32	585	495	16	33	74	BFC-350-32/30K
11	400	25	640	560	16	39	74	BFC-400-25/30K
12	400	32	640	560	16	39	85	BFC-400-32/30K

## Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

09-02-2024